

VETROSPACE M

THE BEST CHOICE FOR 3

Steer clear of distractions with a soundproof workstation. The VETROSPACE M can easily accommodate up to three people for a meeting and is also great as a small private office space or break-out room.

[VIEW ONLINE →](#)



Plug-and-play solutions



Automated, smart CO2-controlled ventilation



Best-in-class soundproofing



Easy access for people with mobility limitations



Superior indoor air quality with G4 and HEPA H13 filters



Antimicrobial LED lighting



Antimicrobial surface nanocoating



ISO 7 indoor air quality performance



TECHNICAL SPECS

Exterior dimensions	W210 / D160 / H240 cm W82.7 / D63 / H94.5 in
Exterior material	LP-laminate
Interior dimensions	W200 / D150 / H220 cm W78.7 / D59 / H86.6 in
Interior material	Acoustic ECOfelt lining
Weight	900 kg 1950 lbs
Indoor surface area	3 m ² 32.2 ft ²
Modular sizes	1-100 m ²
Installation height requirement	>250 cm >98.5 in
Fire safety	UL 723: Class A-C (surface) ASTM E648: Class 1 (flooring)
Electrical safety	IEC 60335-1:2020 UL 962 (E514776)
Seismic safety	Special SEISMIC Certification (2019-0176-COC-01-00), International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)
Patents	US PATENT: 11.492.815 B2 International patents (FI, US, EP, CH, HK, RU)
Door	Patented sliding door
Glass thickness	16.7 mm 0.66 in sound-control safety glass
Sound reduction	Ds: Class A (ISO 23351-1) 43-46dB Rw Lab. STI: 0.03
Ventilation system	Advanced two-stage air filtration (coarse and HEPA 13)
Air flow	Max. 60 l/s
Pressure	Positive air pressure
Cooling/heating	Optional
Lighting	VLD antimicrobial LED
Surface treatment	Photocatalytic antimicrobial nanocoating
Power supply	110-240 VAC / 16 A / 50-60 Hz
Power	70 W average, 300 W maximum
Power sockets	4 as standard

